

CASA™

Blue/black slate with no visible pyrites. The slate offers a textured face with neatly dressed edges. It is an easily workable slate for any roofer who has the pleasure to use it.



Location of the mine/quarry
Northern Spain

DOP Number
32419764

Harmonised Technical Spec Applied
EN123261

Dimension and Dimensional Variation	Complies	Thermal Cycle Class	Code T1
Nominal Thickness Variation	Complies	Sulphur Dioxide Exposure Class	Code S1
Mean MoR Transverse	30 N/mm ²	Non-Carbonate Carbon Content	<2% (0.48%)
Mean MoR Longitudinal	49 N/mm ²	External Fire Performance	Deemed to Satisfy
Water Absorption	Code W1 <<0.6% (0.19%)	Reaction to Fire	Deemed Class A1
Carbonate Content	3.0% (<20%)	Release of Dangerous Substance	None (in normal use)
Intended Use: Slate for discontinuous roofing and cladding		Identification No of Notified Body: SYSTEM 4	

Available Sizes | 7mm thickness

400x250mm

5/6mm thickness

400x250mm

Declaration Of Performance

EC Construction Products Regulation
EN 12326 Roofing & Cladding Slate



The corresponding slate and a half is also available.

In some circumstances, small colour variations may occur due to the product being manufactured from natural source. Before roofing begins ALL- natural slates should be sorted into at least three grades of thickness – in accordance with the BS5534 & BS8000 codes of practice.

Please call the office for any further advice.

5A Caputhall Road, Deans,
Livingston EH54 8AS

www.naturalbychoice.co.uk

info@naturalbychoice.co.uk

01506 374493